



VITCON 2023 PRIMER SB

Solvent Based Bituminous Primer

DESCRIPTION

VITCON 2023 Primer SB is a cold applied bituminous primer, which can be applied either by brush or spray.

USAGE

VITCON 2023 Primer SB is conventionally used as a primer on steel and concrete substrate before applying torch-bond membranes. It provides excellent adhesion to concrete and improves bond between base surface and subsequent overcoats.

ADVANTAGES

- Economical and easy availability.
- Excellent resistance to corrosion elements.
- Sufficient pot life.
- Easy application - Single component.

TECHNICAL DATA

Viscosity (in Ford Cup. No.4, at 25 ⁰ C)	: 20 ± 2 Seconds
Specific Gravity (at 25 ⁰ C)	: 1.10 ± 0.10
Superficial drying time (at 25 ⁰ C)	: 120 Minutes
Complete Drying time (at 25 ⁰ C)	: 24-36 Hours
Finish Appearance	: Semi-gloss
Dry Film Thickness	: 100-150 Micron

APPLICATION METHOD

VITCON 2023 PRIMER SB is to be applied by brush roller or spray without adding any thinner. **VITCON 2023 PRIMER SB** is generally consumed at 200 to 400 gm/m² depending on porosity of concrete.



TECHNICAL RECOMMENDATION

Before applying the primer stir it or shake it. Do not dilute product by any thinner, which may cause alteration in product consistency.

PACKING

VITCON 2023 Primer SB is available in 20 Kg metal cans.

STORAGE

Keep in cool places and airtight containers.

SAFETY PRECAUTIONS

Avoid direct contact with skin. If there is any splash in body, wash with mild soap and plenty of water and take medical attention immediately.